SCR331

The Premier USB Solution















Technical data

Host interface	• Full speed USB (12 Mbps)
	Bus powered device
	CCID compliant
Smart Card	• T=0,T=1 protocol support
Interface	Memory card support through SCM MCARD
	API
	Communication speed up to 344,105 bps
	(PPS, FI parameter)
	• Frequency up to 12 MHz (PPS, DI parameter)
	Support ISO 7816 Class A and AB smart card
Smart Card	8 contacts - ISO location
Connector	Certified for 100,000 insertions
	Sliding contact
Human	One dual state green LED
Interface	
Cable/Power	Cable: I.5m long with USB type A connector
	Power through USB bus
Dimension	• LWH 90 × 70 × 16.5 mm
Operating	0° to 50° Celsius
Temperature	
OS	• Windows® 98, Me, 2000, XP, Server 2003
	• Windows® CE
	MacOS, Linux, Solaris
API	• PC/SC
	CT-API (thru wrapper on top of PC/SC)
	OCF upon request
Approvals	FCC Class B part 15, cULus, CE, VCCI
	• USB
	Microsoft® WHQL Me, 2000, XP, Server 2003
	EMV Level I

US Headquarters SCM Microsystems Inc. 466 Kato Terrace Fremont, CA 94539, USA email: adapter@scmmicro.com Phone +1 510 360 2300 Fax +1 510 360 0211

European Headquarters SCM Microsystems GmbH Oskar-Messter-Str. 13 D-85737 Ismaning, Germany email: sales@scmmicro.de Phone +49 89 9595 5000 Fax +49 89 9595 5555

SCM Microsystems, Japan Inc. 8F Hirakawacho Ronstate, 2-11-1, Hirakawacho-cho, Chiyoda-ku, Tokyo, Japan Postal code: 102-0093 email: sales@scmmicro.co.jp Phone +81 3 3511 8511 Fax +81 3 3511 8516

SCM Microsystems France ZE Athélia II - n° 216, Avenue du Serpolet 13704, La Ciotat, Cedex, France email: sales@scmmicro.fr Phone +33 442 838 000 Fax +33 442 838 001

SCM Microsystems Asia Pte. Ltd. 25 Serangoon North Ave 5 #06-00 Keppel Digihub Singapore 554914 email: sales@scmmicro.com.sg Phone +65 6551 5233 Fax +65 6483 0210

Secure Micro Technologies, India Pvt. Ltd.
Module No. 0308
3rd Floor, D Block-South
Tidel Park
4, Canal Bank Road
Taramani, Chennai 600 113, India
email: sales@scmmicro.co.in
Phone +91 44 2254 0636
Fax +91 44 2254 0645

Overview

The SCR331 is the first of a new family of Smart Card Readers based on SCM's STC II micro controller. This device includes support for multiple interfaces, multiple reader devices and relevant security standards. Together, these features provide SCM with the unique ability to offer high performance and cost effective solutions. In addition, the SCR331 is the industry's first to offer on-board flash. This enables future firmware and application enhancements that guarantee against obsolescence.

The SCR331 offers the best price/performance ratio in the market.

SCR331 Benefits

- On-board flash provides seamless firmware upgrades in the field
- EMV Level | AND PC/SC certification based on a single solution
- High performance
- Fully tested and compliant with all major Smart Cards in the market
- Customizing options: casing, colors, and company logo

The SCM Microsystems Advantage

SCM Microsystems brings over a decade of experience in ASIC and Smart Card Reader development to this unique product, including:

- More than 60 patents
- Support for all current and emerging international standards
- Customer base of global, top tier PC OEMs, systems integrators and Smart Card industry leaders
- Industry endorsed SmartOS™ middleware
- · Direct significant long-term relationships with all leading Smart Card manufacturers and application providers
- High quality mass production capability



MICROSYSTEMS www.scmmicro.com