

"SmartFold"-SCR3500

Portable ID1 contact smart card reader



Features

- Full ISO7816 ID1 smart card reader
- Portable, small ergonomic design
- · CCID compliant
- · Software and functionality fully compatible with SCM's SCR3310v2 reader
- EMV Level 1 certification*
- Customization options: casing colour and company logo
 *ongoing

Typical Applications

The "SmartFold" SCR3500 mini USB reader is a fully ISO7816 compliant contact smart card reader which is perfectly suitable for a wide range of application areas for government, enterprise and home use.

Due to its small design, this ID1 reader is ideal to be bundled with smart cards and software to support large scale project roll outs. Typical applications areas of this reader are in the field of electronic ID cards, social security cards, secure network log-on, e-Banking and online shopping, loyalty and e-Coupon cards as well as for online gaming activities.

Contact Reader

U.S. Headquarters SCM Microsystems Inc. 41740 Christy Street Fremont, CA 94538 USA E-mail scmsales@scmmicro.com Phone +1 510 360 2300 Fax +1 510 360 0211

European Headquarters SCM Microsystems GmbH Oskar-Messter-Str. 13 85737 Ismaning, Germany E-mail sales@scmmicro.de Phone +49 89 9595 5000 Fax +49 89 9595 5555

SCM Microsystems Japan, Inc. GoogolPlex Millennium Building 6F 4-4-20 Shiba, Minato-ku, Tokyo, Japan 108-0014 E-mail sales@scmmicro.co.jp Phone +81 3 6414 6611 Fax +81 3 6414 6612

SCM Microsystems India Pvt. Ltd. Module No. 0506, 0507 & 0508 D' Block South, 5th Floor Tidel Park, 4 Canal Bank Road Taramani Chennai 600113, India E-mail sales@scmmicro.co.in Phone +91 44 2254 0020 Fax +91 44 2254 0029

www.scmmicro.com



"SmartFold"-SCR3500

Technical Data

Interfaces		
Host	USB	 Full speed USB 2.0 (12 Mbps) USB Bus powered device CCID compliant
Smart Card	contact	 T=0, T=1 protocol support Memory card support through SCM MCARD API Communication speed up to 344 kbps (PPS, FI parameter) Frequency up to 8 MHz (PPS, DI parameter)' Support ISO 7816 Class A, B and C smart card 8 contacts - ISO 7816 location Friction contact, 100,000 insertions
Human	optical	• LED (red)
Software	API	PC/SC CT-API (thru wrapper on top of PC/SC)
Operating Systems		 Windows[®] 7 Windows[®] Vista, XP, Server 2003, 2000, ME, 98 Windows[®] Vista, XP, Server2003 (AMD64/EMT64) Windows[®] CE 3.0, 4.1, 4.2, 5.0, 6.0 MacOS, Solaris, Linux 32-bit (2.4.x, 2.6.x)/64-bit
USB Connector		• Type A
Dimensions	L x W x H [mm]	• 48 x 20 x 12
Weight	[g]	• 11
Operating Conditions	Temperature [°C] Humidity [%]	• 0 to 50 • 90 (non-condensing)
Approvals	Functional	 FCC Class B part 15, cULus, CE, VCCI ANZI (SCR3310) ICES-003 Issue4, ClassB USB-IF Microsoft[®] WHQL 2000, XP, Server2003 EMV 2000 Level 1
	Environmental	RoHS, WEEE REACH compliance (SCR3310v2.0)

Technical data are subject to change without notice.

The SCM Microsystems' Advantage

Trusted Partner

- ASIC (application specific IC) and smart card reader development experience since 1990
- · Innovative solutions more than 50 patents filed
- Reliable high-quality mass production capability more than 15 Mio. reader solutions deployed to date
- Active role in standardization committees
- Complex project management expertise e.g. U.S. Department of Defense CAC program, electronic ID applications (ePassport, health card projects, national ID, driver licence)

Support

- Global presence and support
- Product customization options
- Product branding
- Dedicated Research & Development and customer support team
- Strong global partnership network with leading suppliers along the value chain (smart card manufacturers, application providers, system integrators, device manufacturers)

Trusted Products

- Broadest portfolio of security technology products for governments, corporations, financial institutions, small and medium-sized enterprises and individuals around the globe
- Secure smart chip reader design certified and compliant to EMV, Common Criteria, PC/SC, USB
- High-quality products designed to meet the various requirements in the data security area
- Flexible and future proof solutions SCM's SmartOS™ firmware and its own ASIC technology allow in Field upgrades and secure your investment



ALL INFORMATION CONTAINED IN THIS DOCUMENT IS PROVIDED "AS IS"; SCM ASSUMES NO RESPONSIBILITY FOR ITS ACCURACY AND/OR COMPLETENESS. © SCM Microsystems Inc., 2009 0623 rev.1.1 all rights reserved. SCM and SCM Microsystems are trademarks of SCM Microsystems inc. All other trademarks are trademarks of their respective owners. In no event will SCM Microsystems Inc. be liable for damages arising directly or indirectly from any use of the information contained in this document. The SCM Microsystems Inc. homepage can be found at www.scmmicro.com